1990

AIR QUALITY CONTROL FOR ARIZONA

ANNUAL REPORT
AUGUST 1991

HONORABLE FIFE SYMINGTON GOVERNOR STATE OF ARIZONA

ARIZONA DEPARTMENT OF ENVIRONMENTAL QUALITY EDWARD Z. Fox, DIRECTOR

PREPARED BY OFFICE OF AIR QUALITY

ACKNOWLEDGMENTS

The Arizona Department of Environmental Quality extends sincere appreciation to the sampler operators named below for their services, which included operating particulate samplers and mailing the samples collected at the State's monitoring sites.

Ajo

-

Casa Grande

Sam Larson

Clarkdale

Mike Brede & Kim Butts

Douglas (15th Street)

Edmund Garcia & Ray Faxon

Fred Rayfield & W.T. Cain

Flagstaff

Allan Cook, Jeff Fergen, Ron Melcher & ADOT Staff

Grand Canyon-Hopi Point

U.S. National Park Staff

Hayden

Ray Morales

Miami Tailings

David J.H. Fletcher

Montezuma Castle Nat'l Monument

Barbara Monroe & Kathy Reid

Nelson

Rick Schneider

Nogales

Ricardo Maldonado

Organ Pipe Cactus Nat'l Monument

U.S. National Park Staff

Paul Spur

Edmund Garcia & Ray Faxon

Payson

Mike & Jennifer Cavender, Bill Merrifield & Colin

"Buzz" Walker

Prescott

Armando Valadez

Rillito

Carl Gremmler

Safford

B. O'Neill

Sedona

Gordon Fox

Show Low

Cathy Bowles

Yuma

Burton Hale

The Arizona Department of Environmental Quality expresses its appreciation for the assistance of the following companies and agencies and their staff who provided air quality data for this report:

Arizona Portland Cement Company	Tom Brosnan
Arizona Public Service Company	Larry Crisafulli
ASARCO, Incorporated	Melvin Sharp
Century Power Corporation	Prabhu Dayal
Cyprus Miami Mining Corporation	Tom Larsen
Magma Copper Company	Eldon D. Helmer
Maricopa County Health Department	Donald Hopkinson
Phoenix Cement Company	Bernard Ott
Pima County Health Department	David Esposito
Pinal County Air Quality Control District	Martin Godusi
National Park Service	Kristi Gebhart Bobby Carson
Salt River Project	Nils I. Larson
Southern California Edison Company	Stan Marsh
Tucson Electric Power Company	H. Duane Bock

U.S. Environmental Protection Agency Rudolph Boksleitner

TABLE OF CONTENTS

		Tah	le	of	Co	nte	nt	S		_									٠	•		•		•		i iii iv v
I.	BACK																									
	211011																									
	Α.	Leg Air	al	Au	tho	rit	У	•	•	•		•	•	•	•	•	•		•	•	•	•	•	•	•	1
	В.	Air	Qu	al	ity	st	an	da	rd	s		•	•	•	•	•	•	•	•	•	•	•	•	•	•	3
	c.	Sou	rce	s	• •	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	٠	4
II.	PROG	RAM	ACT	IV	ITY	IN	1	99	0	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	6
	Α.	Veh	icl	e i	Emi	ssi	on	s	In	sp	ec	ti	on.	ı F	rc	gr	an	a ((VI	CII	?)	•				6
	В.	OXV	gen	at	ed	Fue	ls		_																	8
	c.	Com	pre	SS	ed	Nat	ur	al	G	as	(CN	G)						•	•	•	•	•	•	•	9
	D.	Tra	ffi	C	Red	uct	io	n/	cl	ea	ın	Αi	r	Ca	mp	oa i	gr	1.	٠	•	•	•	•	•	•	9
	E.	Urb	an	No	nat	tai	nm	en	t	Ar	·ea	. G	ra	ınt	:s		•				•	•	•		•	10
	F.	Rep	ort	s	to	the	L	ea	is	la	tu	re	٠.							•	•	•	•	•		11
	G.	PM1	0 S	Sta	te	Imp	le	me	nt	at	ic	n	Pl	ar	ıs	(2	SII	?s)		•	•			•	•	12
	н.	Pho	eni	x	and	Tu	cs	on	E	rc	wn	ı C	lc	oud	l S	iti	ıdi	Les	s.						•	13
	I.	Pho	eni	x	and	Tu	CS	on	F	M1	0.	st	uc	lie	s											14
	J.	Agr	icu	11 t.	ura	1 0	us	t	Cc	nt	rc	1											•	•		15
	ĸ.	Roa	d r	ານຮ	t. A	bat	em	en	t		_														•	15
	L.	Amb	ier	nt.	Mon	ito	ri	na	70	ua	ίĺi	ŧν	, P	SS	sur	car	106	∍.								16
	м.	Sta	+ i c	ากล	rv	Sou	rc	₂	ĆĈ	mr	11	ar	ıce	<u>.</u>												16
	N.	Air	To	xi	cs.	•	•	•	•	•	•	•	•	•	•	•	•	•		•			•	•	•	19
III.	AIR	QUAL	.ITY	M	ONI	TOF	IN	G	NE	TW	OF	KKE	.	•	•		•	•	•			•	•	•	•	20
	Α.	Mon	i+c	ri	na	Net	MO	rk	S				_													20
	В.	Mon Dat	a F	≀ep	ort	ing	· •	•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	21
IV.	AIR	QUAI	ΙΤΊ	r D	ATA	FC	R	19	90).	•	•	•		•	•	•	•		•	•	•	•	•	•	22
v.	AIR	QUAI	IT?	ľ	REN	DS		•	•		•	•	•			•	•	•	•	•	•	•	•		•	24
	Α.	Car	·hor	n M	onc	xić	le	_	_																	24
	В.	Les	ıd		• :		-							•			•	•					•			24
	c.	Nit	roc	ien	Di	oxi	de	•	•		-															24
	D.	020	nne	,,	• •	22 3				-	•		•			_										25
	E.	DM 1	<u> </u>	•	• •	•	•	•	-	•	-	-		-	•	_	_	•								25
	F.	Sul	-0 • fiii	r D	iox	ide	٠.	•	•	•	•			•	•	•	•								•	

TABLES

Table	1	Ambient Air Quality Standards 27
Table	2	1990 Counties and Towns Monitored 28
Table	3	1990 Carbon Monoxide Data (in ppm) 32
Table	4	1990 Lead Data (in μ g/m³) In TSP or PM10 34
Table	5	1990 Nitrogen Dioxide Data (in μ g/m³)36
Table	6	1990 Ozone Data (in ppm)
Table	7	1990 PM10 Data (in μg/m3)
Table	8	1990 TSP Data - High Volume Sampler (in μ g/m3)
Table	9 .	1990 Sulfur Dioxide Data (in μ g/m³)49
Table	10	1990 Sulfates Data (in μ g/m³) In TSP or PM10
Table	11	PM10 Concentrations In Various Cities 54

FIGURES

Figure	1	Maricopa County Monitoring Network 55
Figure	2	Pima County Monitoring Network 57
Figure	3	State and Industrial Monitoring Networks 59
Figure	4	Carbon Monoxide Concentrations in Phoenix and Tucson 61
Figure	5	Carbon Monoxide Exceedances in Phoenix and Tucson
Figure	6	Lead Concentrations in Phoenix and Tucson 63
Figure	7	Ozone Concentrations in Phoenix, Tucson and Yuma
Figure	8	Ozone Exceedances in Phoenix 65
Figure	9	PM10 Concentrations in Phoenix 66
Figure	10	PM10 Concentrations in Tucson 67
Figure	11	Sulfur Dioxide Exceedances in Hayden, Miami and San Manuel 68

			·

T. BACKGROUND

A. LEGAL AUTHORITY

Arizona derives its authority to regulate air quality from the Federal Clean Air Act and from State Statutes, both of which are described herein. The first Federal Clean Air Act was passed in 1963. It provided for grants to air pollution control agencies and contained the first federal regulatory authority. The Act was amended in 1965, 1967, 1970, 1977, and 1990. One important feature of the Act was the establishment of National Ambient Air Quality Standards (NAAQS) in 1970. These standards which are promulgated by the EPA (Environmental Protection Agency) are set at levels which protect public health and welfare. A brief discussion of the standards is provided in the following subsection B, Air Quality Standards.

Another significant aspect of the Act is the requirement of the states to formulate plans to comply with the NAAQS. Specifically, Section 110 of the Act requires states to adopt and submit to EPA plans which provides for the implementation, maintenance and enforcement of air quality standards within a specific time after standard promulgation. This plan is referred to as the State Implementation Plan (SIP), which consists of several different elements. Some of the more important SIP components are listed below:

- Rules, including enforceable emission limitations and other measures, necessary for attainment and maintenance of the standards.
- 2. Compliance schedules.
- Ambient monitoring and data analysis.
- 4. A permitting program, including the requirement for preconstruction review and disapproval of new or modified sources which would interfere with the attainment or maintenance of air quality standards or would significantly deteriorate air quality.
- 5. Source surveillance.
- Inspection and testing of vehicles.
- 7. Provisions to revise the plan.
- 8. Legal authority to carry out the SIP.
- 9. Prevention of air pollution emergency episodes.

Arizona's SIP contains State statute and rules, county regulations and the nonattainment area plans required for attainment and maintenance of the NAAQS. These documents are transmitted by the Arizona Department of Environmental Quality (ADEQ) to EPA. EPA formally approves or disapproves the SIP revisions through Federal Register notices.

State statutes divide jurisdiction over air pollution sources between the State and the counties. The State has exclusive jurisdiction over air pollution sources having potential total emissions of 75 tons or more per day; air pollution sources owned or controlled by State or local government entities; motor vehicles; and other mobile air pollution sources over which the State has asserted jurisdiction. All other sources come under county authority. Currently Maricopa, Pinal, and Pima Counties have established air pollutant control districts. It should be noted, however, that in other Counties which lack air quality control programs, the State has complete jurisdiction including Apache, Cochise, Coconino, Gila, Graham, Greenlee, La Paz, Mohave, Navajo, Yavapai, and Yuma.

In the Maricopa and Pima Counties nonattainment areas, the reagional planning agencies are required to develop plans to show how the area will attain and maintain the NAAQS. The county and cities and towns in the area must adopt and implement the plan as expeditiously as practicable. For areas which are nonattainment with respect to carbon monoxide or ozone, the plan includes transportation control measures designed to reduce motor vehicle traffic, to alleviate traffic congestion, to promote the use of cleaner fuels, and other strategies. For areas not meeting partic-culate (PM_{10}) standards, control strategies such as paving of roads, re-stricting off-road vehicular traffic, suppressing fugitive dust at construction sites, and other measures are key elements of the plan.

With respect to nonattainment areas, the 1990 Clean Air Act changed several key provisions including:

- Criteria for classifying nonattainment areas;
- Classifications of nonattainment areas;
- · Control measures required for each classification; and
- Deadlines for compliance with NAAQS.

Other major features of the 1990 Clean Air Act addressed the following issues:

- Mobile sources;
- Air toxics;
- · Acid rain;
- · Permits;
- Stratospheric ozone depletion;
- · Visibility Protection;
- Enforcement; and
- · Miscellaneous Provisions.

B. AIR QUALITY STANDARDS

EPA has set NAAQS for six pollutants, which are summarized in Table 1. For each pollutant EPA has adopted primary standards to protect public health and secondary standards to protect public welfare. The states are required to adopt standards which are at least as stringent as the NAAQS. In Arizona, ambient air quality standards are identical to the federal NAAQS.

A brief summary of the health and welfare effects which have been considered prior to setting ambient air quality standards is given below.

Health and Welfare Effects (at ambient concentrations)

<u>Pollutant</u>

Carbon Monoxide

Impairs the ability of blood to carry oxygen in the body. Cardiovascular system is primarily affected, causing angina pain in persons suffering from cardiac disease and leg pain in individuals with occlusive arterial disease. Affects other mammals in a similar manner.

Lead

Damages the cardiovascular, renal, and nervous systems resulting in anemia, brain damage, and kidney disease. Preschool age children are particularly susceptible to brain damage effects. Similar effects observed in other mammals. Other adverse effects on animals, microorganisms, and plants.

Nitrogen Dioxide

Impairs the respiratory system, causing a high incidence of acute respiratory diseases. Preschool children are especially at risk. Damages certain plants and materials. Degrades visibility due to its brownish color and its conversion to nitrate particles. Nitrate particles are also a major component of acid rain.

Ozone

Damages the respiratory system, reducing breathing capacity and causing chest pain, headache, nasal congestion, and sore throat. Individuals with chronic respiratory diseases are especially susceptible to ozone. Injures certain plants, trees, and materials.

Particulates

Causes irritation and damage to the respiratory system, resulting in difficult breathing, inducement of bronchitis, and aggravation of existing respiratory diseases. Also, certain polycyclic aromatic hydrocarbons in particulate matter are carcinogenic. Individuals with respiratory and cardiovascular diseases, children, and elderly persons are at the greatest risk. Soils and damages materials. Impairs visibility. Acid rain particulates damage materials, plants, and trees and acidify surface waters, thereby harming aquatic life.

Sulfur Dioxide

Aggravates asthma, resulting in wheezing, shortness of breath, and coughing. Healthy persons exhibit the same responses at higher exposures. Asthmatics and atopic individuals are the most sensitive groups, followed by those suffering from bronchitis, persons with emphysema, bronchiectasis, cardiovascular disease, the elderly, and children. Damages certain plants and materials. Impairs visibility and contributes to acid deposition due to the its conversion to sulfate particles.

C. SOURCES

1. Carbon Monoxide (CO)

Motor vehicles are by far the major source of CO, followed by minor sources including aircraft, controlled forestry and agricultural burning, industrial facilities, fireplaces, structural fires, railroads and off-road vehicles. Because CO is emitted mainly at ground level, it is trapped at nighttime when the lower atmosphere is stagnant due to a surface-based temperature inversion. As a result, CO concentrations are much greater during evening and early morning hours. Surface-based temperature inversions occur after sunset due to the cooling of the earth's surface as it loses heat by radiation. After sunrise, solar radiation heats the earth's surface and the lower atmosphere, resulting in dissipation of the temperature inversion. Since inversions are more severe during the fall and winter months, CO concentrations are much higher in these months. As a result, standards are exceeded primarily in the period from October through March.

2. Lead

Lead is emitted primarily by motor vehicles (not equipped with catalytic converters) which burn leaded gasoline. Both the use of leaded gasoline and the lead content of this fuel have decreased substantially. Ambient concentrations of lead have declined over time and are well below the standard in Phoenix and Tucson.

3. Nitrogen Dioxide (NO2)

Motor vehicles are the dominant source of NO_2 emissions, followed by power plants, and industrial and commercial facilities. In addition, NO_2 is also derived from the oxidation of NO (nitric oxide) in the atmosphere. NO is emitted by the same sources that emit NO_2 . Concentrations of NO_2 in Arizona are well below the ambient standard.

4. Ozone

Ozone is formed in the atmosphere by the reaction of volatile hydrocarbons with nitrogen oxides (NO and $\mathrm{NO_2})$. This chemical reaction occurs much faster in the presence of sunlight at higher temperatures. Thus, ozone concentrations are greater in the afternoon hours from May to September and occasionally exceed the standard in Phoenix. Days on which ozone concentrations are high are characterized by low wind speeds, late temperature inversion dissipation, and a relatively early wind direction shift. Hydrocarbons and nitrogen oxides, the precursors of ozone, are emitted largely by motor vehicles. Secondary sources of hydrocarbons include gasoline marketing, organic solvent usage, and miscellaneous area sources. For nitrogen oxides, secondary sources include power plants and industrial and commercial boilers.

Particulates

Sources of particulate matter vary widely in Arizona by region and season. In Phoenix and Tucson, motor vehicles exhaust and resuspension of road dust by traffic are the two major sources. Minor sources include construction activity and windblown dust from disturbed desert. In agricultural areas, farming activity is an additional source of fugitive dust whereas fireplaces and woodstoves emit substantial quantities of smoke in northern Arizona. In rural, industrial areas of the state, tailings piles, surface mines, quarries, material handling and storage, ore crushing and grinding, and haul roads are sources of particulate matter. Exceedances of particulate standards in the state occur chiefly in the southern and western desert regions.

6. Sulfur Dioxide (SO₂)

In Arizona, major sources of SO_2 include copper smelters and coal-fired power plants which are located in rural areas with the exception of one coal-fired power plant in Tucson. Generally, SO_2 concentrations near power plants are well below the standards. In the copper smelter areas, however, concentrations have occasionally exceeded the standards, although no violations of the SO_2 NAAQS were recorded in Arizona in 1990.

II. PROGRAM ACTIVITY IN 1990

A. <u>VEHICLE EMISSIONS INSPECTION PROGRAM (VEIP)</u>

The State's VEIP did not undergo any legislative-initiated changes during the 1990 calendar year. However, there were operational changes and improvements in the program due to the issuance of a new contract to perform the mandatory emissions test. As a result, Gordon-Darby, Inc. was awarded this contract for a seven and one-half year period, replacing Hamilton Test Systems.

During 1990, Gordon-Darby worked toward the implementation of their program which commenced January 1, 1991. This included securing real estate for each station and a new waiver lane facility now located on the west side of Maricopa County; building construction and the installation of all of the new equipment, including a computerized testing program; public relations relating to the automotive industry and the Arizona public who were affected by the dramatic change in the emissions testing system; the installation of the system's equipment in all of the waiver lane facilities and the training of the state employees at the waiver lane facilities on the new equipment. A comparison of former and new VEIP contracts shows the following:

NEW	OLD
\$5.40	\$ 7.50
\$5.40	\$24.50
12	11
5 operators	1 operator
Rep.ea. station	1 phone
2 -Phx / 1 -Tuc	1-Phx / 1-Tuc
64	64
All sta.8AM-5PM	3 sta.8AM-3:30PM
	\$5.40 \$5.40

The new contract enhances the service to the public.

Vehicular Inspection/Maintenance Summary - 1990

No. of initial emission tests:	1,684,685
No. of tampering inspections:	1,472,854
No. of vehicles tested by fleet operators:	145,524 (approx)
No. of mechanics trained-proper tuneup procedures:	1,160 (approx)

Improvements in idle emissions of vehicles identified as not meeting standards, as a result of required repairs, were:

50% in CO 45% in HC

The Emission Research Laboratory (Laboratory) completed an extensive "In Use Vehicle Test Program" on the effectiveness of oxygenated fuels in reducing vehicular emission, which were completed November 16, 1990. The Emissions Research Laboratory completed 375 tests on 112 vehicles. Each test followed the Federal Test Procedure (FTP) requiring a minimum of 18 hours to complete. The test involved measurements of hydrocarbons from vehicles inside air tight enclosures, and measurements of hydrocarbon, carbon monoxide, nitrogen oxides, and methane from vehicles driven on a simulated urban driving course with the vehicles operated on a dynamometer. The vehicles tested were a representative group of passenger cars and light duty trucks that passed and failed the Arizona State Emissions Program, and characteristic of the vehicle fleet in the nonattainment areas. The vehicles were tested using the two oxygenated fuels, MTBE and ethanol blend, mandated for the two Arizona nonattainment areas, plus a base unleaded fuel.

Preliminary data analysis revealed that the majority of vehicles tested averaged more than a 20% reduction in carbon monoxide. The ethanol blend provided the highest reductions in carbon monoxide. On various occasions, carbon monoxide reductions on individual vehicles was greater than 60%.

The Laboratory conducted tests on compressed natural gas (CNG) conversion vehicles in the interim period before the initiation of the Winter Reid Vapor Pressure (RVP) Gasoline Test Program. One aspect which the CNG testing has revealed is that dual fueled vehicles (gasoline and CNG) often are misadjusted and the benefit gained from the use of CNG can be nullified when the vehicle is switched back to gasoline fuel.

The Laboratory is also charged with the evaluation of the effect of reducing gasoline volatility on vehicular emissions. The Winter RVP Test Program began in December 1990, and continued until ambient temperatures negated the laboratory's ability to maintain the sub-ambient temperatures required for testing in March. Seventeen "In Use" vehicles, eight fuel-injected and nine carburetted were tested. Duplicate federal exhaust and evaporative tests were performed on each vehicle. Preliminary data reduction from the test revealed significant exhaust and evaporative reductions with the decrease of RVP of gasoline. Because substantial test data was already available which could be evaluated and the federal government mandated lower RVP fuels for nonattainment areas, the Summer RVP Test Program was canceled.

As a result of the Clean Air Act Amendments of 1990, EPA is currently in the process of developing enhanced emissions inspection procedures for use in nonattainment areas. That work has included the development of a potential "transient mode" loaded test, in which a vehicle would be tested on a dynamometer during a short driving trace. As Arizona is the only state now administering a loaded test, we have followed EPA's work closely. This test proposed by EPA to date is quite lengthy and could significantly increase testing fees. The Laborotory is currently working to develop an alternative to EPA's test.

The program will consist of two major segments: The first segment will be the development of the I&M test; and the second segment will be the extensive testing of vehicles for verification. Ideally, the new I&M test will pass or fail the same vehicles that would pass or fail the FTP. The test must also be timely, economical and accurate, without imposing undue hardships on vehicle owners.

B. OXYGENATED FUELS

Oxygenated fuels are gasoline blends that include additives containing oxygen. Alcohols and ethers are examples of such additives. Oxygenated fuels have been demonstrated to be effective at reducing tailpipe emissions of carbon monoxide since the early 1980's. In 1988, the Legislature mandated the use of oxygenated fuels in Phoenix and Tucson, from October 1 through March 31 of each winter season. The Phoenix metropolitan area commenced using oxygenated fuels in October 1989, while the Tucson program commenced in October 1990.

The Legislature also mandated a public education program, to help the driving public understand the nature and value of these fuels. ADEQ with the assistance of the Arizona Department of Weights and Measures, and the Arizona Department of Transportation hired contractors to: 1. Develop a public outreach program using advertising media and printed brochures to explain the purpose of the oxygenated fuels program and the effect of these fuels on vehicle emissions and performance; 2. Create a toll-free information line to answer basic questions about the program and direct callers to other sources of information; and 3. Train automotive technicians regarding these fuels. The program assisted people with the transition to oxygenated fuels, with the vast majority of people approving of their use. Motorists in Maricopa County drove nine billion miles on these fuels in 1990, without any verifiable case of damage to vehicles attributed to the fuels. Over 3,000 automotive technicians were trained in the 1989-1990 season, and about 500 in the 1990-1991 season.

It is estimated that the oxygenated fuels used in Maricopa County (2.3% oxygen by weight) reduced tailpipe emissions of carbon monoxide by an average of 16% across the fleet, while the blends used in the Tucson area (1.8% oxygen) reduced emissions by about 11%. The oxygen content for fuels sold in Maricopa County will increase to 2.7% beginning October 1, 1991, as a result of legislation adopted in 1991 in response to control measures contained in the Federal Implementation Plan (FIP) promulgated by EPA on January 28, 1991. This is expected to reduce carbon monoxide emissions by an additional 3%.

C. <u>COMPRESSED NATURAL GAS (CNG)</u>

CNG, or compressed natural gas, has been identified by the Legislature as a desirable alternative fuel for use by state agencies and government entities throughout Arizona. Each year the ADEQ provides up to \$250,000 in grant awards for the purpose of providing these entities with the financial assistance required to expand existing CNG fleets and related facilities, or to initiate new CNG projects. ADEQ has approved grant funding for CNG conversion programs in Scottsdale, Glendale, Tempe and Tucson. The goal is to establish sufficient fueling facilities and implement conversions in each of these fleets. The Department is scheduling vehicle emissions testing programs for the converted vehicles to quantify emissions reductions. The conversion of buses is a Department priority in both the Phoenix and Tucson metropolitan areas.

D. TRAFFIC REDUCTION/CLEAN AIR CAMPAIGN

One strategy to reduce mobile source pollutants in Arizona's urban areas is to reduce the number of vehicles on the road. During 1990, both Maricopa and Pima Counties received grants from ADEQ's Air Quality Fund to continue implementation of the regional Travel Reduction Program (TRP) and Voluntary No-Drive Day Campaigns.

The Pima County TRP was instituted in 1988 through city and county ordinances, while the Maricopa County TRP was mandated by the Legislature in 1988. The TRPs place requirements on employers of 100 or more employees to "provide each regular employee with information on alternate mode options and travel reduction measures". Alternate mode choices may include transit, car and vanpool opportunities, bicycle, walking, and telecommuting. Other programs, such as the "guaranteed ride home" for workers using bus, carpool, or vanpool, have also been instituted.

In its second year, the Maricopa County TRP program began analyzing its base-year employee survey data compiled in FY 89-90. Preliminary results indicate that of those employees who responded, approximately 81% of all one-way work trips were made by single-occupant vehicles. Surveys submitted in Pima County indicate a similar level of single-occupant vehicle use.

The Voluntary No-Drive Day Campaigns in both Pima and Maricopa Counties complement the Travel Reduction Program. Media and public information networks target the travel-reduction message to the motoring public and employees. "Spare the Air" and "Don't Drive One in Five" have become familiar themes to Pima and Maricopa County motorists respectively.

E. URBAN NONATTAINMENT AREA GRANTS

A.R.S. § 49-551 gives ADEQ authority to use Air Quality Fund Fees to conduct air quality research, experiments and programs to help bring the Tucson and Phoenix areas into compliance with the federal air quality health standards. Cities, towns, counties, and regional planning agencies are eligible to receive grants. A call for proposals was issued in July, 1990. Ten of the 23 proposals received were judged by an interagency committee, as appropriate for funding. Five of the grants were finalized by the end of 1990 and are outlined below.

City of Phoenix - Diesel Particulate Traps for Buses

Anticipated FY 90-91 ADEQ Budget:

\$121,000

Project will install and test five particulate traps on existing diesel engines that power Phoenix Transit buses. The traps collect and oxidize exhaust particulate air pollutants.

City of Tucson - Urban Form

Anticipated FY 90-91 ADEQ Budget:

\$206,000

The Urban Form program is designed to evaluate and mitigate air quality and related impacts of growth through the integration of existing fragmented land use and transportation data bases; creation of evaluation criteria to guide urban development consistent with air quality goals; and research into urban development incentives/disincentives pursuant to air quality goals.

<u>City of Tempe</u> - Transit Planning Using Geographic Information Systems

Anticipated FY 90-91 ADEQ Budget:

\$ 46,700

The City of Tempe, in coordination with the Regional Public Transportation Authority (RPTA), Maricopa Association of Governments (MAG) and Maricopa County, will use a geographic information system application to manipulate data compiled from surveys submitted by City employees for the County's Travel Reduction Program. The analysis will produce more effective travel reduction and transportation planning as well as improved transit routing and scheduling in Tempe.

Maricopa Association of Governments - Vanpools

Anticipated FY 90-91 ADEQ Budget:

\$ 85,000

The Regional Public Transportation Authority (RPTA) has operated a vanpool program since 1987. RPTA, with ADEQ funds will continue to offer vanpooling to commuters through a third-party vanpool provider. The goal of this project is to place up to 30 vanpools in service each transporting a group of 7 to 15 commuters to work each day.

Anticipation FY 90-91 ADEQ Budget:

\$ 25,000

Travel Reduction Program (TRP) Surveys are sent to every employee in businesses with 100 or more employees. A Statutory goal of 5% reduction in single-occupant vehicle use is computed based solely upon completed TRP commuting-mode surveys distributed to every employee; respondents are not randomly selected. This project will determine whether the TRP survey results are representative and predictive of 1) all employees participating in the TRP; and 2) employees of com-panies not participating in the TRP. Results will produce an improved methodology to evaluate the effectiveness of the TRP.

F. REPORTS TO THE LEGISLATURE

ADEQ, with the support of the Arizona Department of Weights and Measures and Department of Transportation, is responsible for developing data and reporting to the Legislature on the following mobile source topics:

1. Feasibility of Control of NOx Emissions from In-Use Vehicles

Summarizes the feasibility of adding a testing element for oxides of nitrogen ($\mathrm{NO_x}$) to the Arizona Vehicle Emissions Testing Inspection Program (VEIP). Report recommends that a $\mathrm{NO_x}$ component not be added at this time.

2. <u>Air Quality Benefits from Expanding Boundaries of the Vehicle Emissions Inspection Program</u>

Concludes that aggressive enforcement of existing testing requirements could have equivalent benefits to and lower costs than the expansion of testing boundaries.

3. <u>Analysis of the Effectiveness of Arizona's Vehicle Emissions</u> <u>Inspection Program (VEIP)</u>

Focuses on the causes of high failure rates in the loaded test portion of the VEIP. Concerns are expressed in the report whether owners of newer model year failures are receiving free repairs to which they may be entitled under the Performance Warranty provisions of the Clean Air Act.

4. The Effects of Reid Vapor Pressure and Oxygenated Fuels on Carbon Monoxide and Hydrocarbon Emissions

Found that use of oxygenated fuels reduces exhaust emissions of carbon monoxide by 25-36% and exhaust hydrocarbon emissions by 15-20%, depending upon the type and condition of the vehicle. Report also describes test plans to determine the effects of gasoline volatility on carbon monoxide emissions.

5. <u>Cost Effectiveness of Carbon Monoxide Reduction Measures in Urban Arizona</u>

Report finds that the Vehicle Emissions Inspection Program is the most cost effective measure, followed by the mandatory use of oxygenated fuels, and the Travel Reduction Program requirements for major employers.

6. <u>Causes of Violations at Monitors</u>

Report concludes that improved traffic flow cannot be expected in the long term to reduce carbon monoxide levels at Tucson and Phoenix monitoring sites.

7. <u>Toxic Emissions from Gasoline Powered Vehicles</u>

Highlights of the report include the findings that oxygenated fuels are expected to significantly reduce emissions of benzene, a known carcinogen, but also increase emissions of aldehydes, some of which are suspected carcinogens.

G. PM10 STATE IMPLEMENTATION PLANS (SIPs)

The 1990 Clean Air Act Amendments, signed on November 15, 1990, set an ambitious one-year deadline for the submittal to EPA of PM_{10} State Implementation Plans (SIPs) for those areas of a state not attaining the National Ambient Air Quality Standards (NAAQS) for PM_{10} (particulate matter with an aerodynamic diameter of 10 microns or less). The SIP must demonstrate that:

- 1. The area will, with the implementation of the plan, attain the NAAQS for PM_{10} by December 31, 1994 or show that attainment by that date is impracticable; and
- Reasonably Available Control Measures (RACM) and Reasonably Available Technology (RACT) are committed to be implemented by December 10, 1993.

The following areas of Arizona have been designated as PM_{10} Nonattainment Areas by EPA and must have SIPs submitted by November 15, 1991:

Ajo	Hayden/Miami*	Paul Spur*	Rillito Yuma
Douglas	Nogales	Phoenix	runa

The following areas of Arizona are proposed as newly designated PM_{10} Nonattainment Areas and must have SIPs submitted 18 months after officially receiving a nonattainment designation by EPA:

Bullhead City

Payson

 $^*\mbox{In 1990, ADEQ}$ submitted \mbox{PM}_{10} SIP revisions for the Hayden and Paul Spur planning areas; EPA is currently reviewing those plans.

H. PHOENIX AND TUCSON BROWN CLOUD STUDIES

Results of the Phoenix urban haze ("Brown Cloud") study conducted from September, 1989 through January, 1990 by Desert Research Institute (DRI) indicate that fine carbon particles are the major contributor to visibility impairment, accounting for 69% of light extinction. Motor vehicle exhaust is the main source of carbon particles in Phoenix, followed to a lesser extent by residential woodburning and other combustion sources such as power plants, industrial processes, meat cooking and aircraft.

In addition to assessing the nature of the Phoenix Urban Haze, this research yielded valuable information concerning the performance of various monitoring instruments and the usefulness of the resultant data. This information will be helpful in designing future, intensive studies of urban haze and in establishing permanent, long-term network. In Phoenix, a permanent network will be installed and operated to monitor visibility year-round, to track long-term trends and to evaluate the effectiveness of air pollution control measures. In order to facilitate this monitoring program, DRI will provide training to ADEQ in the installation and operation of instrumentation and in the interpretation of data.

In Tucson, similar findings were obtained in the pilot urban haze study conducted by DRI during the same period as for the Phoenix study. Carbon particles from motor vehicle exhaust were the dominant visibility impairing species. Minor or insignificant contributors to light extinction included sulfate and nitrate particles and nitrogen dioxide from motor vehicle exhaust, soil particles and carbon particles from wood combustion. It should be noted, however, that these results are based on a more limited degree of sampling, primarily in the central Tucson area. In order to thoroughly assess the characteristics and extent of urban haze in the Tucson metropolitan area, an expanded network is required. Current plans call for comprehensive monitoring to begin in Tucson by January, 1992.

I. PHOENIX AND TUCSON PM10 STUDIES

During the course of the Phoenix and Tucson urban haze studies, DRI also conducted research on ${\rm PM}_{10}$ in these two urban areas. As a result, DRI found that ${\rm PM}_{10}$ concentrations in the Phoenix urban area were generally higher in west and central Phoenix than in Scottsdale. Conversely, the lowest concentrations were measured at remote, upwind sites and at elevated sites in the urban area. At all sites, geological material was the major component of PM_{10} , accounting for 40-60% of measured concentrations at the urban sites. Virtually all of this material was road dust resuspended by vehicular traffic on paved roads in the urban area. Carbonaceous particulate from motor vehicle exhaust was the second largest component, contributing 30-50% of PM_{10} at the urban sites. At least 50% of this material was emitted by diesel-fueled vehicles with the remainder coming from gasoline-fueled vehicles. Vegetative burning was the third largest source of PM_{10} at the two residential sites, west Phoenix and south Scottsdale, where 13-15% of PM_{10} was attributed to this source. However, at the central Phoenix site and the three non-urban sites, it was a negligible source of PM_{10} . This geographical pattern suggests that residential woodburning was the only significant source of PM_{10} from vegetative burning. Besides motor vehicle traffic and residential wood combustion, no significant sources of PM₁₀ were evident. Ammonium nitrate and ammonium sulfate, secondary aerosols derived from gaseous pre-cursors, were generally not detected at significant concentrations.

With respect to long-term PM_{10} monitoring, ADEQ plans to operate dichotomous samplers in order to continually track source apportionment. This will provide a means to evaluate the effective-ness of various PM_{10} control measures. In addition, ADEQ will purchase and operate a recently developed instrument which measures PM_{10} concentrations instantaneously and automatically. Thus, the variation of PM_{10} concentrations with changes in meteorological conditions and PM_{10} emission rates could be correlated accurately, providing greater insight into source apportionment.

J. AGRICULTURAL DUST CONTROL

<u> Alternative Tillage</u>

ADEQ has sponsored several projects investigating alternative methods of agricultural tillage to reduce particulate emissions. The goal of these projects is to quantify the reduction of particulate emissions by comparing emissions during conventional tillage and alternative tillage operations. Alternative tillage may be defined as tillage methods that reduce soil or water loss.

Typically, more than one farm operation is performed during a pass on a field. Fewer passes are performed and less dust is emitted. The alternative operation itself leaves the field in a condition that is less conducive to dust emissions from wind erosion. ADEQ funded the University of Arizona, Department of Agricultural Engineering, to conduct research in the fall of 1990 with alternative tillage equipment. Preliminary results indicate a significant reduction in dust emissions when alternative tillage is used. Research is expected to continue in Fall and Winter 1991-1992.

Revegetation of Retired Farmland

Another program funded by ADEQ was experimental revegetation techniques to prevent dust emissions from retired farmland. The University of Arizona, Agricultural Cooperative Extension has conducted research with different species of grasses and plants to determine a combination of techniques and vegetation that is easily adaptable to the desert croplands once those lands are retired from production. The experiment continued for three years concluding with a final harvest in the spring of 1991. The results from the harvest indicate the plant density per area of retired farmland planted. These densities will be related to dust emission reductions on an areawide basis.

K. ROAD DUST ABATEMENT

The purpose of this program was to determine characteristics of unpaved roads in Arizona, so that potential health effects from particulate emissions and prioritization for control measures can be determined.

The Department contracted with the Midwest Research Institute (MRI) to develop mathematical relationships between particulate concentrations in the ambient air and their causative factors, namely, road characteristics and traffic conditions.

The field testing was conducted in Yuma, Pima and Pinal Counties in 1990 by MRI and the Arizona State University, Center for Advanced Research in Transportation (CART). The relationships derived from this research may be used by Arizona transportation agencies and communities as guidelines for determining control measures for unpaved roads.

L. AMBIENT MONITORING/QUALITY ASSURANCE

Noteworthy progress in the state's ambient monitoring/quality assurance program was achieved in 1990, initiated by the hiring of a quality assurance coordinator. Subsequently, the state's quality assurance procedures were closely reviewed and revised as needed. As a result, significant improvements, especially in PM_{10} sampling and analysis, were implemented. In addition, auditing of state monitoring sites was transferred from the instrumentation group to the quality assurance coordinator in order to provide independent checks on the performance of monitoring instruments. Finally, the auditing program was expanded to include checks on industrial and county monitoring sites.

M. STATIONARY SOURCE COMPLIANCE

Surveillance of all stationary major sources was continued throughout the state for the purpose of determining compliance with state and federal regulations. ADEQ also regulates minor sources in counties where no local air pollution control program exist. These counties were: Apache, Cochise, Coconino, Gila, Graham, Greenlee, La Paz, Mohave, Navajo, Yavapai and Yuma. Elements of this regulatory program include:

- Unannounced inspections of air pollution sources;
- Investigations in response to complaints from public, private and legislative contacts;
- Observations and reviews of emission tests of regulated sources;
- Review and determination of conditions for operating permits of existing facilities;
- Review of installation permit applications and determination of conditions for the construction of new sources;
- Technical assistance and cooperation with local and federal regulatory agencies; and
- NESHAPS (National Emission Standards for Hazardous Air Pollutants) inspections of regulated sources.

During 1990, field surveillance expanded substantially due to the hiring of additional staff. As a result, determinations of the compliance status of state-regulated sources were improved considerably. This enhancement is reflected in the work activity data for 1989 and 1990, shown in the table at the end of this section.

Significant enforcement actions completed in 1990 included the following:

- Order of Abatement was developed against VanLandingham and Associates for improper asbestos demolition in Flagstaff. The issue was resolved when proper procedures were used. Potential hazard to the environment was averted.
- Order of Abatement was developed against Arizona Public Service Company (APS). The APS issues involved operation and maintenance procedures at the Cholla Generating Station and was resolved during 1991 with a Consent Order of Abatement.

In addition to field compliance and enforcement activities, the stationary source data management system was upgraded. This improvement was achieved primarily by providing a computer for each workstation and connecting each computer to a local area network.

Presently, there are approximately 550 air pollution sources regulated under the state air pollution permit program. These consist of 36 major sources, 312 minor sources and 202 portable sources. The major sources consist of six power plants, three copper smelters, two Portland Cement companies, eight copper mines, one paper mill and one printing operation. In addition, one petroleum refinery is in the process of obtaining an installation permit.

In order to process permit applications promptly, three additional permit engineer positions were authorized by the Legislature this year. For the purpose of defining permit conditions more specifically, the permit process has been modified to include an emission rate table in each permit. This emission rate table includes a numeric emission limitation expressed in pounds per hour and tons per year for each air contaminant and each emission point.

The requirement to limit emissions of trace metals was included in the Cyprus Miami Mining Corporation permit to protect the health and welfare of the public living around the smelter.

ADEQ Air Compliance Efforts

MEASUREMENT	JUL89- SEP89	OCT89- DEC89	JAN90- MAR90	APR90- JUN90	JUL90- SEP90	OCT90- DEC90
Field Inspections Central Northern Southern TOTAL	5 42 <u>36</u> 83	0 34 <u>65</u> 99	16 49 <u>26</u> 91	33 35 <u>34</u> 102	43 24 <u>31</u> 98	55 14 <u>48</u> 117
Notices of Violation	10	12	12	19	17	21
Orders of Abatement	0	0	0	0	0	2
NESHAP Notifications	22	57	43	46	73	137
Complaints Central Northern Southern TOTAL	37 13 <u>15</u> 65	55 13 <u>21</u> 89	30 11 <u>32</u> 73	51 8 <u>23</u> 82	38 5 <u>21</u> 64	53 3 <u>23</u> 79
Compliance Tests	16	10	7	7	14	21
Smoke School Class Attendance Field Attendance CERTIFICATIONS	20 20 17	0 28 26	39 56 40	89 130 28	43 75 56	5 44 21

N. AIR TOXICS

A study to determine ambient concentrations of formaldehyde and acetaldehyde was conducted in Tucson from December 1990 through March 1991. The purpose of the study was to assess the effects of oxygenated fuels use on ambient aldehyde concentrations. Samples were collected over a 24-hour period on cartridges containing a chemically coated packing which reacts with aldehydes. The Tucson study was a follow-up to a baseline study conducted in December, 1989 through February, 1990 prior to the mandatory use of oxygenated fuels. Nitrogen oxides (NO $_{\rm x}$) concentrations were also measured at the aldehyde site. The corresponding NO $_{\rm x}$ concentrations were used to normalize the aldehyde concentrations for a "before and after" comparison. Results indicated that formaldehyde concentration levels were significantly higher in 1990-91 compared to 1989-90, but acetaldehyde concentrations were not. However, due to limited monitoring data, it cannot be concluded that the use of oxygenated fuels in Tucson was the cause of increased ambient formaldehyde concentrations.

For the purpose of long-term monitoring of urban-related air toxics, a search for a centrally located site in Phoenix was conducted. As a result, an inactive City of Phoenix water well compound at 4530 North 17th Avenue will be used to sample for air toxics and criteria pollutants. Also, a review of methodology, equipment and space requirements for laboratory analysis of air toxic samples was completed. This review indicated that the State Laboratory, Arizona Department of Health Services, must be provided substantial funds to develop and install the necessary methods and equipment. An alternative is to contract with private laboratories to perform the various analyses, but this would not be cost effective for a broad-based, long-term monitoring program.

III. AIR QUALITY MONITORING NETWORKS

A. MONITORING NETWORKS

In Arizona, ambient air monitoring is conducted by a number of governmental agencies and regulated industries. A list of these monitoring network operators and the areas monitored is given below.

Agency or Industry

Area Monitored

Arizona Portland Cement Co.

Rillito

Arizona Public Service Co.

Joseph City

ASARCO, Inc.

Hayden

Century Power Corp.

Springerville

Cyprus Miami Mining Corp.

Miami

Magma Copper Co.

San Manuel

Maricopa County Health Dept.

Phoenix Metro. Area

National Park Service

National Monuments

and Parks

Pima County Health Dept.

Tucson Metro. Area

Pinal County Air Quality

Control District

Pinal County

Salt River Project

Page and St. Johns

Southern California Edison Co.

Bullhead City, AZ and Laughlin, NV

Tucson Electric Power Co.

Tucson

Maps indicating the locations of the Phoenix, Tucson and statewide monitoring stations are provided in Figures 1, 2, and 3. The Maricopa and Pima County networks are operated primarily to monitor urban-related air pollution. In contrast, the industrial networks are operated to monitor emissions from certain industrial facilities. State monitors are employed for a variety of purposes, including urban, industrial, rural and background surveillance. Finally, the National Park Service sites in Arizona have the unique objective of monitoring visibility in pristine areas in accordance with federal regulations for visibility protection. Included in this activity are measurements of various optical parameters as well as pollutant concentrations.

B. DATA REPORTING

Ambient air quality data collected in 1990 by the various networks above are summarized in Section IV of this report. In addition, Maricopa and Pima Counties and some of the companies publish annual reports which include summaries of their data.

Raw data files are maintained by each of the network operators and are available upon request to them. In addition, the U.S. Environmental Protection Agency (EPA) stores raw data submitted quarterly by Maricopa and Pima Counties and the State. EPA analyzes these data for the purposes of evaluating progress in attaining and maintaining the NAAQS and reporting trends in air quality to the President and Congress.

Maricopa and Pima Counties report pollutant concentrations in the Phoenix and Tucson urban areas each day to the public via television, radio, newspapers and telephone. The data are reported in pollutant standard index (PSI) units, that is, units of concentrations relative to the standards. These reports include the descriptor words "good", "moderate", "unhealthy", "very unhealthy", or "hazardous", depending on pollutant levels.

The industrial operators submit either monthly or quarterly data reports to the state, depending on the type of facility. In addition, they are required to report any exceedance of an air quality standard by the next working day. The report includes an explanation of the causes of the exceedance and corrective actions to be taken, if possible, to prevent future occurrences.

IV. AIR QUALITY DATA FOR 1990

Table 2 lists the counties and towns monitored in the state and the pollutants for which data are listed.

1990 data summaries, which are tabulated in Tables 3 through 10, consist of the following:

- Mean concentrations for the calendar year;
- Highest concentrations for shorter time intervals;
- Number of exceedances of air quality standards; and
- Number of samples collected or hours monitored.

In the data summaries, the following abbreviations and footnotes were used:

General

NA	Not Applicable
NR	Not Reported

Operators

APC APS ASARCO CENT CM Magma Maricopa	Arizona Portland Cement Company Arizona Public Service Company ASARCO Century Power Corporation Cyprus Miami Mining Corporation Magma Copper Company Maricopa County Department of Health Services, Bureau of Air Pollution Control
NPS Pima	National Park Service Pima County Health Department, Air Quality Control District
Pinal SRP SCE State TEP	Pinal County Air Quality Control District Salt River Project Southern California Edison Company Arizona Department of Environmental Quality Tucson Electric Power Company

Equipment

Carbon Monoxide

GFC

Gas filter correlation

Nitrogen Dioxide

Chem

Chemiluminescent

<u>Ozone</u>

Chem

Chemiluminescent

UV

Ultraviolet absorption

TSP

Hi-Vol

High volume air sampler

PM10

SA321B

Sierra Andersen 321B hi-vol Sierra Andersen 1200 hi-vol

SA1200 Wed Dichot Imp.

Wedding hi-vol Dichotomous Improve

Sulfur Dioxide

Coul Flame Coulometric

Flame photometric

Fluor

Fluorescent

Footnotes:

- a. New site
- b. Site terminated
- c. Mean value based on a limited number of samples
- d. Site operated on a seasonal schedule
- e. Site operated on an event basis
- f. Units for Pb are ng/m3
- g. Data for Pb and SO_4 are for particles smaller than 2.5 um

V. AIR QUALITY TRENDS

A. CARBON MONOXIDE

During the past 10 years in Phoenix, concentrations have declined substantially as indicated by the graphs in Figures 4 and 5. In these graphs the second highest 8-hour concentrations and the number of exceedances of the 8-hour standard were plotted. Because it is a neighborhood scale site, the trend for the Roosevelt Street monitor is more consistent than for the Indian School Road monitor, a microscale site. This also explains why concentration are lower at the Roosevelt Street site.

In Tucson concentrations decreased moderately through 1987 and then leveled out through 1990 (see Figures 4 and 5). Another major difference in Tucson is the fact that the second highest 8-hour concentrations declined below the standard (9ppm) to 7ppm. As a result, no violation of the 8-hour standard has occurred in Tucson since 1984. Because it is usually the highest recording site, the 22nd and Alvernon site data were plotted in Figures 4 and 5.

B. <u>LEAD</u>

In both the Phoenix and Tucson urban areas, lead concentrations have continued to decline as illustrated in Figure 6. This decreasing trend, which began in 1978, is due to the increasing use of unleaded gasoline in catalyst-equipped cars and the reduced lead content in leaded gasoline.

C. NITROGEN DIOXIDE

For Phoenix no long-term database is available to assess nitrogen dioxide trends. Monitoring sites were shut down in 1985 due to difficulties in operating and maintaining instruments. Moreover, data collection in the 1981 to 1985 period was significantly limited. This probably explains why annual average levels fluctuated between 30 and 59 $\mu\,\mathrm{g/m^3}$ during these years. The only conclusion apparent from these data is that the Phoenix metro-politan area was in compliance with the annual standard, 100 $\mu\,\mathrm{g/m^3}$.

Monitoring in the Phoenix metropolitan area was resumed in 1990 at three sites after new instruments were purchased. Average concentrations for these sites ranged from 30 to 36 $\mu\,\mathrm{g/m^3}$ for six months in 1990.

In Tucson a long span of monitoring data is available, and the annual average values obtained are given below:

	<u>1982</u>	<u>83</u>	<u>84</u>	<u>85</u>	<u>86</u>	87	<u>88</u>	<u>89</u>	<u>90</u>
Annual average:	40	38	36	30	36	36	32	34	36
$(\mu \text{ g/m}^3)$									

Site: 22nd/Craycroft

These data suggest that NO_2 concentrations decreased from 1982 through 1985, and then increased in 1986. Thereafter, annual means tended to vary randomly between 32 and 36 μ g/m³. Compliance with the annual standard is evident for the Tucson urban area.

D. OZONE

Referring to Figure 7, a gradual reduction in ozone levels in the Phoenix metropolitan area is apparent. This pattern is also reflected in the numbers of exceedances of the standard which are plotted in Figure 8. However, it should be noted that higher concentrations have been monitored at two special sites operated by the State in recent years. For example, in 1990 these two sites recorded second high 1-hour concentrations of 0.14 and 0.13ppm, compared with a second high of 0.11ppm from the Maricopa County network. Also, one of these state-operated sites (600 N. 40th St.) measured six exceedances while the other (2035 N. 52nd St.) monitored five exceedances. In contrast, only one exceedance was detected at each of three county sites in 1990.

In Tucson second high values have not changed as much as in Phoenix, with only a slight reduction is indicated in Figure 7. Exceedances of the ozone standard in Tucson are not plotted in Figure 8 because only one was measured (in 1982) during this period. In Yuma no discernible change since 1980 is evident if the 1980 value is considered to be an anomaly (see Figure 7). It is interesting to note that the Yuma readings are virtually the same as those for Tucson despite the large difference in populations.

E. <u>PM10</u>

PM₁₀ levels at the two oldest sites in Phoenix, 4732 S. Central and 1845 E. Roosevelt, have declined appreciably since 1986 (see Figure 9). By 1990 both sites measured annual averages below the level of the standard. Furthermore, the S. Central monitor indicated compliance with the annual standard because the 3-year average for 1988-1990 was $49~\mu~g/m^3$. However, the Roosevelt site was still not in compliance due to a 3-year average of $54~\mu~g/m^3$. The W. Earll data,which covers only the past three years, also exhibits a downward trend except in 1989. The increase in 1989 at this site is probably due to nearby street construction. As a result of the high annual average in 1989, the W. Earll site did not attain the standard in 1990 (1988-1990 average was $56~\mu~g/m^3$).

In Tucson PM_{10} concentrations did not follow any consistent pattern from 1988 through 1990 (see Figure 10). Since they are the oldest PM_{10} sites in Tucson, data for the Prince Rd. and Orange Grove Rd. monitors were plotted in Figure 10. Both sites were in compliance with the annual standard for the 1988-1990 period.

For other cities in Arizona, annual average PM_{10} concentrations are listed in Table 11. Of all these cities, Hayden is the only one which reflects a long-term trend, a substantial decrease from 1985 through 1990. Data for the rest of the sites indicate very little change or inexplicable fluctuations from year to year. Some of these irregular variations (Douglas in 1989, Paul Spur in 1990, and Rillito in 1989) are probably due to a limited number of samples. Finally, it is interesting to note that concentrations dropped significantly at the Casa Grande, Hayden, Nogales, Rillito and Safford sites in 1990.

F. SULFUR DIOXIDE

Major improvements were observed in Hayden and San Manuel where no exceedances of the 3-hour standard were monitored in 1990 (see Figure 11). In contrast, 1989 had been the worst year during the past five years in these two smelter towns. Miami continues to display the best conditions of the three smelter towns in Arizona, with only one exceedance of the standard (in 1987) in the past five years.

Summary of Ambient Air Quality Standards State and Federal Standards In $\mu g/m^3$ (and ppm)

Pollutant	Averaging Time	Primary	Secondary
Carbon Monoxide ^b	1-hr. 8-hr.	40 (35) 10 (9)	40 (35) 10 (9)
Nitrogen Dioxide	Annual	100 (.05)	100 (.05)
Ozone	1-hr.	235 (.12)	235 (.12)
PM ₁₀	24-hr. / Annual	150 / 50	150 / 50
Sulfur Dioxide	3-hr. 24-hr. Annual	365 (.14) 80 (.03)	1300 (.5)
Lead	Calendar Quarter	1.5	1.5

Summary of Emergency Episode Levels State and Federal In $\mu g/m^3$ (and ppm)

Pollutant	Averaging Time	Alert	Warning	Emergency	Significant Harm
Carbon Monoxide	1-hr. 4-hr. 8-hr.	 (15)	(30)	 (40)	(125) (75) (50)
Nitrogen Dioxide	1-hr. 24-hr.	1130(.6) 282(.15)	2260(1.2) 565(.3)	3000(1.6) 750(.4)	3750(2.0) 938(.5)
Ozone	1-hr.	400(.2)	800(.4)	1000(.5)	1200(.6)
PM ₁₀	24-hr.	350(-)	420(-)	500(-)	600(-)
Sulfur Dioxide	24-hr.	800(.3)	1600(.6)	2100(.8)	2620(1.0)

 $^{^{\}rm a}$ Standards are not to be exceeded more than once per year with two exceptions. In the case of ozone and PM_{10} , compliance is determined by the number of days on which the 0_3 or PM_{10} standard is exceeded. The number of exceedance days per year, based on a 3-year running average, is not to exceed 1.0.

b In mg/m³ (and ppm)

Table 2
1990 Counties and Towns Monitored

					I	Τ		- I	T								
Sulfur Dioxide	A A A A A A A A A A A A A A A A A A A		×	×								×				×	
TSP			×	×								×	×				
PM10		×	×	×		×	×	×		×	×	×			×	×	>
Ozone		×	×								×	×					
Nitrogen Dioxide			×	×								×					
Lead		×		A TOTAL DESIGNATION OF THE PROPERTY OF THE PRO		×											
Carbon Monoxide																	
County and Town	APACHE:	Petrified Forest	St. Johns	Springerville	COCHISE:	Chiricahua	Douglas	Paul Spur	COCONINO:	Flagstaff	Grand Canyon	Page	Sedona	GILA:	Hayden	Miami	

Table 2 (Cont'd)
1990 Counties and Towns Monitored

County and Town	Carbon Monoxide	Lead	Nitrogen Dioxide	Ozone	PM10	TSP	Sulfur Dioxide
GILA (CONT'D):							
Tonto (NM)		×			×		
Winkelman							×
GRAHAM:							
Safford					×		
MARICOPA:							
Glendale	×			×	×		
Mesa	×			×	×		
Phoenix	×	×	×	×	×	×	×
Scottsdale	×		×	×	×		
MOHAVE:							
Bullhead City			×		×	×	×
Holiday Shores			×	×	×	×	×
Riviera					×	×	×
NAVAJO:							
Joseph City					×	×	
Show Low		-4010-2	- Laboratoria		×		

Table 2 (Cont'd)
1990 Counties and Towns Monitored

Table 2 (Cont'd)
1990 Counties and Towns Monitored

Carbon Monoxide L	H	Lead	Nitrogen Dioxide	Ozone	PM10	TSP	Sulfur Dioxide
	<u> </u>						
					×		
					×		
						×	
						×	
						>	
						4	
				×	×		
	-						

Table 3
1990 Carbon Monoxide Data (in ppm)

				1-HR	8-HR	NUMBER OF	Number
	Site Location	Operator 1	Method	AVEKAGE Max 2ndHi	Ma	Day Times	Sa
Hwy. d	2039 W Lewis	State	GFC	12.0 11.5	8.8 7.8	0 0	3549
	6000 W Olive	Maricopa	GFC	8.4 7.7	5.0 4.8	0 0	7697
	Broadway & Brooks	Maricopa	GFC	5.1 3.4	2.6 2.5	0 0	5293
	4732 S Central	Maricopa	GFC	9.5 8.5	5 5.4 5.3	0 0	8177
	1845 E Roosevelt	Maricopa	GFC	13.2 12.7	7 9.5 8.8	0 0	8444
	601 E Butler Dr	Maricopa	GFC	11.6 11.	3 5.6 5.5	0 0 9	8591
	2750 W Indian School Rd	Maricopa	GFC	12.8 12.8	3 11.6 10.0	4 4	6239
	3847 W Earll	Maricopa	GFC	10.9 10.9	9.1 8.6	0 0 9	8177
	2857 N Miller	Maricopa	GFC	11.9 10.8	8 7.8 7.7	0 0 2	8200
	13665 N Scottsdale Rd	Maricopa	GFC	5.9 5.	9 3.0 2.9	0 0 6	8699
	24301 N Alma School Rd	Maricopa	GFC	5.5 5.	1 1.9 1.8	3 0 0	2420
	150 W Congress	Pima	NDIR	13.8 9.	3 4.4 4.3	3 0 0	8009
	22nd & Craycroft	Pima	NDIR	6.8 6.	2 3.1 3.	1 0 0	7955
	22nd & Alvernon	Pima	NDIR	12.8 11.	7 6.8 6.	5 0 0	8337
	346 N Cloverland	Pima	NDIR	6.8 6.	3 3.1 3	0 0 0.	4806

Table 3 (Cont'd)

1990 Carbon Monoxide Data (in ppm)

County and City	Site Location	Operator Method Max	Method	1-F	JH.	8-HR NUN AVERAGE EXCI Max 2ndHi Day	NUMBER OF EXCEEDANCES Day Times	Number of Samples
PIMA (CONT'D):								
Tucson	2745 N Cherry	Pima	NDIR	7.7	7.6	4.5 4.3	0 0	4949
Tucson	Broadway & Craycroft	Pima	NDIR	10.0	9.7	6.7 6.1	0 0	8366
Theson	4829 N Sabino Canyon Rd P	Pima	NDIR	5.1	4.8	3.0 3.0	0 0	6236
Tucson	12101 N Camino deOste	Pima	NDIR	2.1	1.8 1.6	1.6 1.6	0 0	5619
PINAL:								
Casa Grande	Airport - N Pinal Ave	Pinal	GFC	3.0	2.9 2.7	2.7 2.5	0 0	4080

STATE AND FEDERAL STANDARD (ppm):

1-Hour Average

8-Hour Average

Table 4

1990 Lead Data (in $\mu g/m^3$) In TSP or PM_{10}

vay Ranch Point W Olive E Roosevelt S Central				-	1 2	e	3 4	1 2	2	3 4	4
ified Frst. 1 mi. N of Park SE: icahua NM Faraway Ranch INO: d Canyon NM Hopi Point o Maintenance Stat coPA: dale 6000 W Olive nix 1845 E Roosevelt nix 4732 S Central	Park										
icahua NM Faraway Ranch INO: d Canyon NM Hopi Point OPA: dale 6000 W Olive nix 1845 E Roosevelt		NPS	PM10	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R
icahua NM Faraway Ranch INO: d Canyon NM Hopi Point O Maintenance Stat OPA: dale 6000 W Olive nix 1845 E Roosevelt nix 4732 S Central											
d Canyon NM Hopi Point Maintenance Stat OPA: Gale 6000 W Olive nix 1845 E Roosevelt nix 4732 S Central	nch	NPS	PM10	N/R	N/R	N/R	Ņ/R	N/R	N/R	N/R	N/R
d Canyon NM Hopi Point O Maintenance Stat OPA: dale 6000 W Olive nix 1845 E Roosevelt nix 4732 S Central											
OPA: dale 6000 W Olive nix 1845 E Roosevelt		NPS	PM10	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R
Maintenance Stat 6000 W Olive 1845 E Roosevelt 4732 S Central		·									
6000 W 1845 E 4732 S	e Station	NPS	PM10	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R
6000 W 1845 E 4732 S								:			
1845 E 4732 S	.ve	Maricopa	PM10	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R
4732 S	sevelt	Maricopa	TSP	0.05	0.02	0.01	0.07	13	10	8	9
4732 S			PM10	0.03	0.0	N/R	N/R	14	12	N/R	N/R
	ıtral	Maricopa	PM10	0.02	0.0	0.02	0.02	14	12	14	16
Phoenix 1826 W McDowell	owell	Maricopa	TSP	0.08	0.0	0.05	0.09	11	13	13	11
Phoenix 3847 W Earll	:11	Maricopa	PM10	0.02	0.02	0.02	0.03	15	15	15	14
Scottsdale 2857 N Miller Rd		Maricopa	PM10	0.01	0.01	0.01	0.02	14	13	15	15

Table 4 (Cont'd)

1990 Lead Data (in $\mu g/m^3$) In TSP or PM_{10}

County and City	site Location	Operator IN	IN	QUAR 1	QUARTERLY AVERAGE 1 2 3 4	AVERAGE	AGE 4	NUMBER 1 2	NUMBER OF SAMPLES 1 3 4	SAMPLES	LES 4
PIMA:											
Saguaro NM	Rincon Mountain Unit	NPS	PM10	N/R	N/R	N/R	PM10 N/R N/R N/R N/R N/R N/R N/R	N/R	N/R	N/R	N/R
Tucson	1016 W Prince Rd	Pima	TSP	N/R	N/R	N/R	TSP N/R N/R 0.05 0	0	0	0	8
Tueson	1016 W Prince Rd	Pima	PM10	0.03	0.02	00.00	PM10 0.03 0.02 0.00 0.00 15	15	10	13	Н
Tucson	Broadway & Swan	Pima	PM10	0.00	00.0	00.00	PM10 0.00 0.00 0.00 0.01 15	15	10 12	12	16

STATE AND FEDERAL STANDARD $(\mu g/m^3)$: (Primary and Secondary)

Calendar Quarter Average 1.5

Table 5

1990 Nitrogen Dioxide Data (in $\mu g/m^3$)

County and City	Site Location	Operator	Method	Average	Maximum 1-HR 24	-HR	No. of 1-HR Samples
APACHE:							
St. Johns	Mesa Parada	SRP	Chem	9	23	6	6697
Springerville	Airport	CENT	Chem	4	32	6	7496
Springerville	4 mi NE of town	CENT	Chem	4	51	13	7832
Springerville	1 mi NNE of unit 1 stack	CENT	Chem	4	58	6	8498
Springerville	1 mi ESE of unit 1 stack	CENT	Chem	4	83	15	8330
Springerville	1 mi SSE of unit 1 stack	CENT	Chem	4	72	15	8597
Springerville	12.2 mi SE of unit 1 stack	CENT	Chem	4	38	1.5	1660
COCONINO:							
Page	Glen Canyon Dam	SRP	Chem	3	54	24	7147
MARICOPA:							
Arizona Hwy.ª	2039 W Lewis	State	Chem	43°	387	83	3807
Phoenixª	1845 E Roosevelt	Maricopa	Chem	30°	212	88	4890
Phoenixª	3847 W Earll	Maricopa	Chem	35°	162	98	3782
Scottsdale	2857 N Miller	Maricopa	Chem	34°	203	81	3900
MOHAVE:							
Bullhead City	224 N Main	SCE	Chem	36	169	75	8492

Table 5 (Cont'd)

1990 Nitrogen Dioxide Data (in $\mu g/m^3$)

· (CI TNOO) - MOHANIA	Site Location	Operator Method Average 1-HR 24-HR	Method	Average	Maxımı 1-HR	1M 24-HR	No. or 1-nk Samples
	1436 Tonto Dr	SCE	Chem	1	167	102	6395
PIMA:							
on	22nd & Craycroft	Pima	Chem	36	214	211	8150
	150 W Congress	Pima	Chem	51	218	80	2429
	4591 N Pomona Ave	Pima	Chem	41	182	150	7302

STATE AND FEDERAL STANDARD $(\mu g/m^3)$: (Primary and Secondary)

Annual Average 100

Table 6
1990 Ozone Data (in ppm)

County and City	Site Location	Operator	Method	1-HR MAX Day	MAX 2nd HI Day	Number of Exceedances	Number of Samples
APACHE:							
Petrified Frst ^a	1 mi from Visitor Cntr	NPS	ΔΩ	.10	. 09	0	7814
St. Johns	Mesa Parada	SRP	ΔΩ	60.	60.	0	7759
COCHISE:							
Chiricahua NM	Western entrance to NM	EPA	UV	.14	60.	н	8347
COCONINO:							
Grand Canyon	2 mi W of Hopi Point	NPS	ΩΛ	.07	.07	0	7169
Grand Canyon	2 mi W of Hopi Point	EPA	ΔΩ	60*	60.	0	8646
Page	Glen Canyon Dam	SRP	ΔΩ	.07	.07	0	8576
MARICOPA:							
Glendale	6000 W Olive	Maricopa	ΔΩ	.13	.11		8026
Mesa	Broadway & Brooks	Maricopa	UV	.10	60.	0	7364
Phoenix ^d	2035 52nd St	State	ΔΩ	.17	.14	Ŋ	2849
Phoenix	1845 E Roosevelt	Maricopa	ΔΩ	.11	.11	0	7800
Phoenix	601 E Butler	Maricopa	ΔΩ	.11	.11	0	8553
Phoenix ^d	600 N 40th St	State	ΔΩ	.16	.13	9	2681
Phoenix	3847 W Earll	Maricopa	ΔΩ	.13	.12		8554

rable 6 (Cont'd)
1990 Ozone Data (in ppm)

Samples Number 7406 6135 1354 8455 7724 8357 8207 7948 8390 8552 7868 7962 8353 of Exceedances Number 0 0 0 0 0 0 0 0 0 0 0 0 -MAX 2nd HI Day .08 .10 .09 60. .07 60. 60. .10 10 • 00 .11 .11 .11 .08 • 09 .10 .10 • 09 .10 .10 .09 .09 N/R .13 117 11 .11 MAX Day 1-HR Operator | Method Δ N n 20 ΔΩ Ω Δ S Ω A Ω S N 20 Maricopa Maricopa Maricopa Maricopa Maricopa State Pima Pima Pima Pima Pima Pima Pinal NPS Indian School Rd Sabino Canyon Rd Camino deOeste 24301 N Alma Schood Rd Trl Pinal Ave Scottsdale Rd Gila Bend Hwy Spanish Craycroft Houghton Location Congress Central N Pomona 2857 N Miller z old 1 ß 12101 N Airport 13665 N <u>|</u> త 3 Ŋ Ø ≤ 11330 150 W 22nd 4829 4591 3315 3905 926 4732 MARICOPA CONT'D: 闰 Grande Grande Saguaro NM Scottsdale County and City Scottsdale Scottsdale Phoenix Phoenix Tucson Tucson Tucson Tucson Tucson Tucson PINAL: Casa Casa PIMA:

Table 6 (Cont'd)

1990 Ozone Data (in ppm)

County and City	Site Location	Operator Method		1-HR MAX Day	MAX 2nd HI Day	Number Number of of Exceedances Samples	Number of Samples
YUMA:							
Yuma ^d	1485 Second Ave	State	ΔΩ	.10	60.	0	2748

STATE AND FEDERAL STANDARD: The standard is .12ppm (235 $\mu g/m^3$) for the maximum daily 1-hour (Primary and Secondary) concentration, not to be exceeded more than three times in three years. No more than 1.0 exceedances per year over the last three years is

permitted.

Table 7 1990 PM₁₀ Data (in $\mu g/m^3$)

County and City	Site Location	Operator	Method	Annual Arithmetic Mean	24-HR AVERAGE Max 2ndHi	NUMBER OF EXCEEDANCES 150 µg/m3	Number of Samples
APACHE:							
Petrified Frst	1 mi. from Visitor Cntr	NPS	Imprve	96	28	0	35
St. Johns	Mesa Parada	SRP	Dichot	N/A			
St. Johns	Patterson Wellfield	SRP	Dichot	N/A			
Springerville	Coyote Hills 10.5m SSW of stack	Cent	Dichot	19°	74 63	0	337
Springerville	Plant 1 mi NE of stack	Cent	Dichot	33°	126 77	0	59
COCHISE:							
Chiricahua NM		NPS	Imprve	ွစ်	21	0	32
Douglas	City Park	State	SA1200	38°	133 113	0	44
Paul Spur	Housing area	State	SA322	79°	261 205	4	39
COCONINO:							
Flagstaff	Cherry & Agassiz	State	Wedd'g	29	77 70	0	51
Grand Canyon	Hopi Point	NPS	Imprve	ာ့	24	0	40
GILA:							
Hayden	Jail	State	Wedd'g	39	66 64	0	55
Miami Tailings	Southwest Gas Yd-Hwy 88	State	SA1200	27°	63 58	3 0	44

Table 7 (Cont'd)

 PM_{10} Data (in $\mu g/m^3$)

County and City	Site Location	Operator	Method	Annual Arithmetic Mean	24-HR AVERAGE Max 2ndHi	NUMBER OF EXCEEDANCES 150 $\mu \mathrm{g/m3}$	Number of Samples
GILA (CONT'D):							
Payson	County courthouse	State	SA321B	29	287 182	5	54
Tonto	Maintenance Station	NPS	Imprve	11°	24	0	37
GRAHAM:							
Safford	523 Tenth Ave	State	SA321B	28	87 57	0	53
MARICOPA:							
Chandler	1475 E Pecos Rd	Maricopa	SA1200	49	117 114	0	57
Glendale	6000 W Olive	Maricopa	SA321B	44°	81 77	0	16
Mesa	Broadway & Brooks	Maricopa	SA1200	36	61 60	0	58
Phoenix	4732 S Central	Maricopa	SA321B	40	92 75	0	56
Phoenix	3847 W Earll	Maricopa	SA321B	9†	96 94	0	59
Phoenix	1845 E Roosevelt	Maricopa	SA321B	°94	89 73	0	37
Scottsdale	2857 N Miller Rd	Maricopa	SA321B	3.7	65 64	0	57
Scottsdale	13665 N Scottsdale Rd	Maricopa	SA1200	33	150 89	0	57
Scottsdale ^b	24301 N Alma School Rd	Maricopa	SA321B	20	35 34	0	37
MOHAVE:							
Bullhead City	224 N Main	SCE	SA321B	39	143 139	0	61

Table 7 (Cont'd) 1990 PM_{10} Data (in $\mu g/m^3$)

				Annual	24-HR AVERAGE	NUMBER OF EXCEEDANCES	Number
County and City	Site Location	Operator	Method	Mean	Max 2ndHi	150 µg/m3	Samples
MOHAVE (CONT'D):			•				A STATE OF THE STA
Holiday Shores	1436 Tonto Dr	SCE	SA321B	33	109 76	0	09
Riviera	Fort Mohave	SCE	SA321B	31	144 71	0	61
NAVAJO:					ALLEGE THE STATE OF THE STATE O		
Joseph City	Third & Tanner	APS	Wedd'g	21	65 61	0	61
Show Low	Deuce of Clubs Ave	State	SA1200	22	59 47	0	46
PIMA:							
Ajo	Well Rd	State	SA321B	44°	121 112	0	44
Corona De Tucsn	22000 S Haughton	Pima	SA1200	16	53 49	0	50
Green Valley	245 W Esperanza	Pima	SA1200	19	61 59	0	56
1	Visitor's Center	State	SA321B	23	108 108	0	52
1 13	8820 W Water	State	SA321B	40	94 70	0	51
Rillito	Gremmler Residence	CAL-MAT	Wedd 'g	30	143 99	0	327
Saguaro NM	3905 S Old Spanish Trl	NPS		N/R	N/R N/R	R N/R	N/R
Tucson	Broadway & Swan	Pima	SA1200	29	88 73	0	56
Tucson	150 W Congress St	Pima	SA1200	38	134 117	0	299
Tucson	Golf Link & Harrison	Pima	SA1200	25	68 61	0 1	28

Table 7 (Cont'd) 1990 PM_{10} Data (in $\mu g/m^3$)

County	Site Location	Operator	Method	Annual Arithmetic Mean	24-HR AVERAGE Max 2ndHi	NUMBER OF EXCEEDANCES 150 $\mu \mathrm{g/m}^3$	Number of Samples
DIMA (CONTID):							
	. 5m F. Trv'aton &Alvrnon	TEP	SA321B	27	63 51	0	59
100001		Pima	SA321B	38	134 116	0	284
Idesoli	W Prince	Pima	SA1200	42°	89 75	0	44
Tacson T	S 6th Ave	Pima	SA1200	46	144 108	0	52
Tucson	2nd St & Palm Ave	Pima	SA1200	38	81 72	0	51
Tucson	7290 E Tanque Verde	Pima	SA1200	26	77 58	0	59
PTNAL:							
Apache Tunction	County Court	Pinal	Wedd'g	23°	59 50	0	45
		State	Wedd'g	32	75 57	0	56
- 1	1	Pinal	Wedd'g	37	182 102	П	56
	ind Courthous	Magma	Dichot	12°	27 16	0 9	14
Stanfield	County Courthouse	Pinal	Wedd 'g	38	126 114	0	49
SANTA CRUZ:							
Nogales	US Post Office	State	SA321B	52	175 108	T	52
YAVAPAI:							
Clarkdale	Clarkdale Fire Station	State	Wedd'g	28°	141 120	0 0	41

Table 7 (Cont'd)

1990 PM_{10} Data (in $\mu g/m^3$)

and City Location		Operator Method	Method	Annual Arithmetic Mean	24-HR AVERAGE Max 2ndHi	R NUMBER OF Number (GE EXCEEDANCES of 2ndHi 150 μg/m3 Samples	Number of Samples
YUMA:							
Yuma 2795 Avenue B	В	State	SA321B	57	270 118	L	50

FEDERAL STANDARDS $(\mu g/m^3)$: Ann (Primary and Secondary)

Annual Arithmetic Mean 24-Hour Average 50

Table 8

1990 TSP Data High Volume Sampler (in $\mu g/m^3$)

County and City	Site Location	Operator	Annual Geometric Mean	24-HR Max 2ndHi	Number of Samples
APACHE:					
St. Johns	Airport	SRP	15	52 47	60
St. Johns	Mesa Parada	SRP	10	58 36	59
St. Johns	Patterson Wellfield	SRP	11	65 30	61
Springerville	Airport	Cent	17	94 93	50
Springerville	4 mi NE of town	Cent	6	65 51	49
Springerville	1 mi NNE of unit 1 stack	Cent	19	73 60	59
Springerville	12.2 mi SE of unit 1 stack	Cent	7	58 47	55
COCONINO:					
Page	Glen Canyon Dam	SRP	14	66 45	52
Page	Airport	SRP	40	166 150	09
Sedona	Post Office	State	31°	88 61	20
MARICOPA:					
Phoenix	1845 E Roosevelt	Maricopa	101°	182 169	38
Phoenix	1826 W McDowell	Maricopa	109	235 204	49

Table 8 (Cont'd)

1990 TSP Data High Volume Sampler (in $\mu g/m^3$)

County and City	Site Location	Operator	Annual Geometric Mean	24-HR Max 2ndHi	Number of Samples
MOHAVE:					
Bullhead City	224 N Main	SCE	88	315 230	61
Holiday Shores	1436 Tonto Dr	SCE	62	293 150	09
Riviera	Fort Mohave	SCE	58	313 185	09
NAVAJO:					
Joseph City	3rd St N & Tanner	APS	50	267 128	61
PIMA:					
Green Valley ^b	245 West Esperanza	Pima	30	143 140	46
Sahuarita	Junior High School	Pima	33	244 109	56
Tucson	3401 W Orange Grove	Pima	82°	312 212	45
Tucson	1810 S Sixth Ave	Pima	81°	175 151	44
Tucson	Second St & Palm Ave	Pima	70°	180 161	45
Tucson*	1016 W Prince	Pima	62°	88 88	6
PINAL:					
Mammoth	County Courthouse	Pinal	37	122 101	L 50
Marana	Pinal Air Park	Pinal	58	186 160) 46

Table 8 (Cont'd)

1990 TSP Data High Volume Sampler (in $\mu g/m^3$)

County and City	Site Location	Operator	Annual Geometric Mean	24-HR of Max 2ndHi Samples	Number of Samples
YAVAPAI:					
Nelson	.3 mi W of lime plant	State	74	318 284	48
Prescott	city Administration	State	44°	135 102	102 45

rable 9

1990 Sulfur Dioxide Data (in $\mu g/m^3$)

SRP Fluor
Cent Fluor
Cent Fluor
stack Cent Fluor
stack Cent Fluor
stack Cent Fluor
stk Cent Fluor
SRP Fluor
ASARCO Fluor
ASARCO Fluor
Hayden Junctions ASARCO Fluor
Montgomery Ranch ASARCO Fluor
State
State

Table 9 (Cont'd)

1990 Sulfur Dioxide Data (in $\mu g/m^3$)

	Site Location	Operator	Method	Annual Average	MAX 3-Hr 24-Hr	NO. OF EXCEEDANCES 3-Hr 24-Hr Days Times	r 1-Hr s Samples
٠,,	Jones Ranch	Cyprus M	Fluor	12	730 132	2 0 0	8760
	Whtfld/Burch Pmp Sta	Cyprus M	Fluor	2	87 1	1 0 0	8760
	Town Site	Cyprus M	Fluor	4	430 54	0	8760
' '	1 mi N Jct 77 & 177	ASARCO	Fluor	37	1153 292	0	8707
	1845 E Roosevelt	Maricopa	Fluor	8	56 34	4 0 0	6615
!							
	224 N Main	SCE	Fluor	2	202 39	0 0	8513
	1436 Tonto Dr	SCE	Fluor	е	126 18	0	47
, , ,	Fort Mohave	SCE	Fluor	\$	131 21	0	ין וכ
)
	3905 S Old Spanish Trail	NPS	Coul	N/R	N/R N/R	N/R N/R	R N/R
	22nd & Craycroft	Pima	Fluor	2	52 21	0	8478
	Courthouse	Magma	Fluor	9	184 220	0 0	8750
)

Table 9 (Cont'd)

1990 Sulfur Dioxide Data (in $\mu g/m^3$)

PINAL (CONT'D): Oracle San Manuel San Manuel Golf Course	Мадта			3-Hr 24-Hr	Days Times	Samples
nuel nuel	gma gma					
		Fluor	8	177 181	0 0	8747
		Fluor	20	1257 222	0 0	8746
	Magma	Fluor	22	660 123	0 0	8750
משונתבד חחושות בחוושו שושר	Magma	Fluor	16	763 96	0 0	8753
San Manuel Minesite	Magma	Fluor	12	413 87	0 0	8752
San Manuel LDS Church	State	Fluor	13	1053 139	0 0	8998
San Manuel Elks	Magma	Fluor	32	1227 209	0 0	8749
San Manuel Hospital	Magma	Fluor	33	916 60	0 0	8751

STATE AND FEDERAL STANDARDS (μg/m³): Primary Secondary

Annual Average 80

24-Hour Average 365

3-Hour Average

1300

51

Table 10

1990 Sulfates Data (in $\mu g/m^3$) in TSP and PM_{10}

County and City	Site Location	Operator	NH	Annual Average	24-HR AVERAGE Max 2ndHi	Number of Samples
APACHE:						
Petrified Forst	1 mi. N of Park Hdgrtrs	NPS	PM10	N/R	N/R N/R	N/R
COCHISE:						
Chiricahua	Faraway Ranch	NPS	PM10	N/R	N/R N/R	N/R
Douglas	City Park	State	PM10	0.9°	7.9 3.6	39
Paul Spur	Housing area	State	PM10	1.7°	5.4 3.8	15
COCONINO:						
Grand Canyon	Hopi Point	NPS	PM10	N/R	N/R N/R	N/R
GILA:						
Hayden	Jail	State	PM10	2.0	6.1 5.2	55
Miami Tailings	Southwest Gas Yd-Hwy 88	State	PM10	2.4°	6.7 5.9	29
Tonto	Maintenance Station	NPS	PM10	N/R	N/R N/R	N/R
GRAHAM:						
Safford	523 Tenth Ave	State	PM10	0.5°	2.0 2.0	17
MARICOPA:						
Glendale	6000 W Olive	Maricopa	PM10	4.4°	9.3 8.6	16
Phoenix	1845 E Roosevelt	Maricopa	PM10	2.8°	5.5 3.5	24

Table 10 (Cont'd)

1990 Sulfates Data (in $\mu g/m^3$) in TSP and PM_{10}


County and City	Site Location	Operator	H	Annual Average	24-HR AVERAGE Max 2ndHi	Number of Samples
MARICOPA CONT'D:						
Phoenix	4732 S Central	Maricopa	PM10	2.5°	5.6 3.6	5 19
Phoenix	3847 W Earll	Maricopa	PM10	3.3°	7.3 6.2	34
Scottsdale	2857 N Miller Rd	Maricopa	PM10	3.3°	6.1 5.5	5 17
PIMA:						
Ajo	Well Rd	State	PM10	0.4°	3.3 2.8	3 14
Organ Pipe NM	Visitors Center	State	PM10	1.1	3.7 3.6	5 55
Rillito	8820 W Water	State	PM10	1.9	5.0 4.7	53
Saguaro	Rincon Mountain Unit	NPS	PM10	N/R	N/R N/R	R N/R
Tucson	.5 m E Irvgtn & Alvrnon	TEP	PM10	2.5	5.9 5.1	59
PINAL:						
Casa Grande	401 Marshall Rd	State	PM10	0.7°	3.4 3.3	21
SANTA CRUZ:					100000000000000000000000000000000000000	
Nogales	US Post Office	State	PM10	1.6	5.1 4.7	52
YAVAPAI:						
Nelson	3 mi W of lime plant	State	TSP	2.6	5.5 5.4	48
YUMA:						
Yuma	2795 Avenue B	State	PM10	1.9°	4.6 3.9	18

TABLE 11 ${\rm PM}_{10} \mbox{ Concentrations in Various Cities} \\ \mbox{ Annual Arithmetic Mean } (\mu {\rm g/m}^3)$

SITE	1985	1986	1987	1988	1989	1990
Ajo	41	36	39	42	41	44
Bullhead City				37	52	39
Apache Junction			22	22	16	23
Casa Grande		60	36	44	43	32
Clarkdale					24	28
Douglas (City Park)	62	59	52	57	55	38
Flagstaff	39	38	29	21	24	29
Hayden	68	80	56	52	46	35
Joseph City			20	25	26	21
Nogales	56	76	72	69	63	52
Organ Pipe	18	16	17	16	19	23
Paul Spur	106	111	56	79	122	79
Payson			40	77	79	67
Rillito	66	55	59	69	94	40
Safford	49	40	32	42	44	28
Show Low		32	25	23	23	22

^a Mean value based on a limited number of samples.


Annual standard - 50 $\mu \text{g/m}^3$



Map Key for Figure 1 Maricopa County Monitoring Network

Map Number	Site
1	1845 East Roosevelt - Phoenix
2	4732 South Central - Phoenix
3	3315 West Indian School - Phoenix
4	6000 West Olive - Glendale
5	3847 West Earll - Phoenix
6	601 East Butler - Phoenix
7	13665 North Scottsdale - Scottsdale
8	2857 North Miller - Scottsdale
9	Broadway & Brooks - Mesa
10	1826 West McDowell - Phoenix
11	24301 North Alma School - Scottsdale
12	1475 East Pecos - Chandler
 13 *	2039 West Lewis - Phoenix
14*	2035 North 52nd Street - Scottsdale
15 *	600 North 40th Street - Phoenix


^{*} State operated



Map key for Figure 2 Pima County Monitoring Network

Map Number	Site
1	150 West Congress
2	22nd & Craycroft
3	22nd & Alvernon
4	2745 North Cherry
5	1810 South 6th Avenue - South Tucson
6	2nd Street & Palm
7	1016 West Prince
8	3600 North Silverbell - Silverbell Park
9	4591 North Pomona
10	3401 West Orange Grove
11	346 North Cloverland - Highland Park
12	4575 East Broadway
13	Broadway & Craycroft
14	4829 North Sabino Canyon
15	7290 East Tanque Verde
16	2181 South Harrison
17	2200 South Houghton - Corona de Tucson
18	350 West Helmet Peak - Sahuarita Jr. High School
19	241 West Esperanza - Green Valley
20	12101 North Camino de Oste

Figure 3
State and Industrial Monitoring Networks



Map Key for Figure 3 State and Industrial Monitoring Networks


Map		
Number :	County	Town
1	Apache	Petrified Forest
2		St. Johns
3		Springerville
4	Cochise	Chiricahua
5		Douglas
6		Paul Spur
7	Coconino	Flagstaff
8		Grand Canyon
9		Page
10		Sedona
11	Gila	Hayden
12		Miami
13		Payson
14		Tonto
15		Winkelman
16	Graham	Safford
17	Mohave	Bullhead City
18		Holiday Shores
19		Riviera
20	Navajo	Joseph City
21		Show Low
22	Pima	Ajo
23		Organ Pipe
24		Rillito
25		Saguaro N.M.
26	Pinal	Apache Junction
27		Casa Grande
28		Mammoth
29		Marana
30		Oracle
31		San Manuel
32		Stanfield
33	Santa Cruz	Nogales
34	Yavapai	Clarkdale
35		Montezuma Castle
36		Nelson
37		Prescott
20	37	T7

Yuma

Yuma


38

CARBON MONOXIDE CONCENTRATIONS IN PHOENIX AND TUCSON FIGURE 4



STANDARD IS 9 PPM

CARBON MONOXIDE EXCEEDANCES IN PHOENIX AND TUCSON FIGURE 5




STANDARD IS 9 PPM

LEAD CONCENTRATIONS IN PHOENIX AND TUCSON




Standard Is 1.5 (ug/m3)

IN PHOENIX, TUCSON AND YUMA OZONE CONCENTRATIONS FIGURE 7




STANDARD IS .12 PPM

FIGURE 8 OZONE EXCEEDANCES FOR PHOENIX 5 SITE NETWORK




STANDARD IS .12 PPM

FIGURE 9 PM10 CONCENTRATIONS IN PHOENIX




Standard is 60 (ug/m8)

FIGURE 10 PM10 CONCENTRATIONS IN TUCSON



Standard Is 50 (ug/m3)

SULFUR DIOXIDE 3 - HR EXCEEDANCES IN SMELTER TOWNS FIGURE 11



Air Quality Standard is 1300 ug/m3 (3hr)

	ì
	:
	:
,	
•	
